

RIBBON BLENDER MACHINE (WECAN ENGINEERING SOLUTIONS – AHMEDABAD DIVISION)

Salient Features:-

- U Shaped bin is constructed from Stainless Steel SS316/SS304 of suitable dimensions.
- Helical / Double helical ribbon for homogeneous mixing.
- Consisting of suitable 3 phase or 1 phase motor coupled to suitable worm gear.
- Mounted on suitable ISMC Section Stand, with protective covers for belts, motor, gear box.
- Discharge through SS316 butterfly valve of suitable size (Optional).

Model	RB05	RB25	RB50	RB100	RB150	RB200	RB500	RB1000
Working Capacity in kg.	5	25	50	100	150	200	500	1000
Gross Volume in Itr.	12	65	125	225	375	500	1250	2500
Working Volume in ltr.	10	50	100	200	300	400	1000	2000
Motor Capacity in HP.	0.5	1	2	3	5	5	10	20
Ribbon	Single	Single	Single	Single	Double	Double	Double	Double
Inlet Lid Cover	Yes							
Discharge Butterfly Valve	2 inch	3 inch	4 inch	6 inch	6 inch	6 inch	8 inch	10 inch
Power Supply.	3 Ø – 440V							



LAB GMP MODEL RANGE FROM 1 KG TO 25 KG



GMP MODEL RANGE FROM 25 KG TO 1000 KG